

Atty. Ref.:HSJ9-2003-0235US1, 60717.342801

Page 3 of 11

Amendments to Claims:RECEIVED
CENTRAL FAX CENTER

OCT 18 2006

Please amend the claims as in the following listing:

What is claimed is:

- 1 1. (Currently amended) A magnetic head comprising:
2 a read sensor which is of Current Perpendicular to the Plane (CPP) configuration
3 including:
4 at least one primary pinned layer;
5 a barrier layer;
6 a free layer;
7 an in-stack biasing structure having net magnetic moment $dM=0$, which
8 acts to stabilize said free layer by exchange coupling.
- 1 2. (Original) The magnetic head of claim 1, wherein:
2 said in-stack biasing structure includes paired layers of opposite magnetic
3 orientation which are separated by a spacer layer, such that the net magnetic moment of
4 said paired layers is substantially zero.
- 1 3. (Original) The magnetic head of claim 1, wherein:
2 said $dM=0$ corresponds to a dT less than 5×10^{-10} meters, where magnetic
3 thickness $T = M \times t$, and M equals magnetization, t equals thickness of material, and dT
4 is the differential in the layer thicknesses.
- 1 4. (Original) The magnetic head of claim 1, wherein:
2 said in-stack biasing structure includes a self-pinned layer pair.
- 1 5. (Original) The magnetic head of claim 1, wherein:
2 said at least one primary pinned layer includes a pair of primary pinned layers,
3 separated by a spacer layer.
- 1 6. (Original) The magnetic head of claim 5, further comprising:
2 at least one layer of AFM material which acts to pin said pair of primary pinned
3 layers.
- 1 7. (Original) The magnetic head of claim 5, wherein:
2 said pair of primary pinned layers are self-pinned layers.
- 1 8. (Canceled)
- 1 9. (Original) A disk drive comprising:
2 at least one hard disk;
3 at least one magnetic head adapted to fly over said hard disk for writing data on
4 said hard disk, and having an air bearing surface, said magnetic head including:

Atty. Ref.: HSJ9-2003-0235US1, 60717.342801

Page 4 of 11

- 5 a read sensor which is of Current Perpendicular to the Plane (CPP)
6 configuration including:
7 at least one primary pinned layer;
8 a barrier layer;
9 a free layer;
10 an in-stack biasing structure having $dM=0$, which acts to stabilize
11 said free layer by exchange coupling.
- 1 10. (Original) The disk drive of claim 9, wherein:
2 said in-stack biasing structure includes paired layers of opposite magnetic
3 orientation which are separated by a spacer layer, such that the net magnetic moment of
4 said paired layers is substantially zero.
- 1 11. (Original) The disk drive of claim 9, wherein:
2 said $dM=0$ corresponds to a dT less than 5×10^{-10} meters, where magnetic
3 thickness $T = M \times t$, and M equals magnetization, t equals thickness of material, and dT
4 is the differential in the layer thicknesses.
- 1 12. (Original) The disk drive of claim 9, wherein:
2 said in-stack biasing structure includes a self-pinned layer pair.
- 1 13. (Original) The disk drive of claim 9, wherein:
2 said at least one primary pinned layer includes a pair of primary pinned layers,
3 separated by a spacer layer.
- 1 14. (Original) The disk drive of claim 13, further comprising:
2 at least one layer of AFM material which acts to pin said pair of primary pinned
3 layers.
- 1 15. (Original) The disk drive of claim 13, wherein:
2 said pair of primary pinned layers are self-pinned layers.
- 1 16. (Canceled)
- 1 17. (Canceled)
- 1 18. (Canceled)
- 1 19. (Canceled)
- 1 20. (Canceled)
- 1 21. (Canceled)